





## TECHNICAL DATA SHEET

### Category : Booths & Pods

### Product 2 : Zest

#### Composition:

- Base : Plywood
- Core : Acoustic Foam (Polyurethane)
- Finish : Fabrics
- Applications : Wall Mount with Interlocking Clips
- Worktop:
  - Base : Plywood
  - Top & Bottom : Laminates
  - Colors : Black, Oak & White
  - Edges : Finished with edgebands

#### Patterns & Dimensions:

- **Variant 1: Small**
  - Overall : 700 x 600 x 1170 mm (L x W x H)
  - Worktop : 620 x 200 x 20 mm (L x W x T)
  - Worktop height : 95 mm from the base
- **Variant 2: Large**
  - Overall : 700 x 600 x 1800 mm (L x W x H)
  - Worktop : 620 x 200 x 20 mm (L x W x T)
  - Worktop height : 725 mm from the base

#### Performance:

- Fire Resistance:
  1. Plywood
- **IS 5509:2000 (with Amendments)** | Time for second ignition: >30 minutes | Conforms to Indian fire-resistance standards for interior plywood
  2. Acoustic Foam (polyurethane)
- **CA TB 117-2013 Section III** | Flammability of resilient fire materials - Pass | Flame retardant in upholstered Furniture – Pass
- **BS 5852: Part 2. 1982** | Flammability Test: Pass



## TECHNICAL DATA SHEET

### 3. Fabrics

- Category A+
- **BS 5852 Part 1: 1979 Ignition Source 0 & 1** | Details: Cigarette Test & Match Test | Result: PASS on both tests | Test Number: 423681
  
- Category A
- **BS 5852 Part1: 1979 Ignition Source 0 & 1** | Details: Cigarette Test & Match Test | Result: PASS on both tests | Test Number: 187662
  
- Category B
- **AS/NZS 1530.3:1999** | Details: Simultaneous test for Ignitability, Flame Propagation, Heat Release & Smoke Release | Result: Passed | Test Number: 19-001329

### **Sustainability:**

- **Certifications & Compliance:**
  - LEED v4: Supports EQ Credit (Low-Emitting Materials)
  - Certified Low VOC materials
  - EPD & HPD certified
  - Declare Label compliant
  - USGBC LEED compliant