





## TECHNICAL DATA SHEET

### Category : Lights

### Product 8 : Hexo

#### Composition:

- Base : 100% PET (60% Recycled Content)
- Applications : Ceiling Mounted
- Accessories : Clutch Wire Systems

#### Dimensions:

- (S) : Ø600 x 76 x 99 mm (L x T x H)
- (L) : Ø1200 x 76 x 99 mm (L x T x H)

#### Light Technicals:

- Life Span : 50000 hours
- Diffuser : PMMA
- UGR : <19
- Voltage : 220-240 V
- CRI : 80/90
- CCT : 3000K, 4000K, 6000K
- Performance (LED) : Based on 4000K
- (S): Ø570 mm : 30W / 3600 lm
- (L): Ø1170 mm : 90W / 10800 lm

#### Performance:

1. Fire Resistance:
  - **ASTM E84- 2021** | Flame Spread Index: Class 1 or A | Smoke Developed Index: Class 1 or A
  - **BS EN 13501-1:2018** | Classification: B – s1, d0
  - **AS/NZS 1530.3:1999** | Flame Spread Index: 0 | Smoke Index: 2
2. VOC Emissions:
  - **CDPH Standard Method v1.2** | Section 01350 – Low-emitting materials for schools and offices

#### Sustainability:

- Certifications & Compliance:
  - LEED v4: Supports EQ Credit (Low-Emitting Materials)
  - Certified Low VOC materials
  - EPD & HPD certified
  - Declare Label compliant
  - USGBC LEED compliant